

TRITON BARRIER®



➤ A crashworthy portable barrier that exceeds NCHRP 350, TL-2, the Triton Barrier is an easy to use, water-filled, portable plastic barrier with an internal steel frame for work zone applications. It is so easy to install that a three-person crew can deploy over 183m in just one hour. The bright white and orange sections provide superior visibility. The Triton Barrier helps to prevent vehicle penetration into work areas where crews are present.

➤ BENEFITS / FEATURES

- Tested for use at 100km/h at angles of up to 15 degrees for passenger vehicles and lightweight pickup trucks.
- Provides positive, crashworthy protection for workers and equipment – does not allow penetration into work areas.
- Absorbs collision energy and redirects errant vehicles – reduces severity of impact for motorists.
- Fast deployment – 183m per hour with just 3 worker.
- Modular design allows use in varied lengths for both straight and curved applications.
- No cranes or heavy equipment required for deployment
- Certified as its own end treatment.
- Transition hardware available for attachment to guardrail or concrete barrier.
- Internal steel frame – no additional assembly required.
- Bright orange and white sections provide superior visibility.
- Effective in all weather conditions, even when frozen solid.



➤ SPECIFICATIONS

Length	2m
Height	0.8m
Width	0.5m
Empty Weight	65kg
Full Weight (Water)	610kg
Water Ballast	550 litres

The above are general specifications for the QuadGuard System. Additional information is available in the Design, Installation and Maintenance Manuals for this system. Contact Armco Road Safety Products for details.

